

SEETONG EUROPA S.L.U. CIF B13734926 CALLE JACINTO BENAVENTE 1, PETRER
ALICANTE ESPAÑA CP 03610 TEL +34 667053043 INFO@SMART-DOMOHOUSE.COM

IMPORTADOR PARA MÉXICO: ALEJANDRO ENRIQUE SERRANO GARCIA, RFC
SEGA720208H81, CALLE ANALZINGO 16, COLONIA ANALCO, CUERNAVACA
MORELOS, MÉXICO CP 62166 TEL +52 9986946706 EMAIL
ALEJANDRO.SERRANO@SMART-DOMOHOUSE.COM

FICHA TÉCNICA MODELO :

T4Q78X-DJ-ST-P/4 3.6mm METAL WHITE IP CAMERA IP67 POE 4MP HS 85258090



SEETONG EUROPA S.L.U. CIF B13734926 CALLE JACINTO BENAVENTE 1, PETRER
ALICANTE ESPAÑA CP 03610 TEL +34 667053043 INFO@SMART-DOMOHOUSE.COM

IMPORTADOR PARA MÉXICO: ALEJANDRO ENRIQUE SERRANO GARCIA, RFC
SEGA720208H81, CALLE ANALZINGO 16, COLONIA ANALCO, CUERNAVACA
MORELOS, MÉXICO CP 62166 TEL +52 9986946706 EMAIL
ALEJANDRO.SERRANO@SMART-DOMOHOUSE.COM

Cámara mini bala AI de 4.0MP con soporte

Lente H.265+, 3,6mm F1.4 Starlight. Micrófono incorporado;

1 interfaz Ethernet RJ45 10M / 100M, 1 puerto de 12 V CC, 4 LED de matriz de puntos con chip LED dual, puede admitir el cambio de luz entre IR y luz blanca.

Carcasa de metal, nivel de protección IP67, espacio de almacenamiento requerido de 6 ~ 12 GB para grabación de video de 24 horas

Detección de cuerpo humano AI, que activa una alarma de luz cuando se detecta un ser humano, reduce significativamente la tasa de falsas alarmas.

- ◆ **Micrófono incorporado, admite sincronización de audio y video;**
- ◆ **Apertura avanzada F1.4, optimiza el brillo de la imagen, con un mejor rendimiento en entornos con poca luz**
- ◆ **Admite 3 modos de visión nocturna: luz dual inteligente/infrarrojos/visión nocturna a todo color**
- ◆ **Búsqueda rápida de objetivos para la reproducción**
- ◆ **Carcasa de aleación de aluminio, con alta disipación de calor.**

4.0MP AI mini bullet camera with bracket

H.265+,F1.4 Starlight lens. built-in microphone;

1 RJ45 10M/100M Ethernet interface, 1 DC 12V port, 4 dual LED chip dot matrix LEDs, can support light switching between IR and white light.

Metal casing, IP67 protection level, 6~12GB required storage space for 24-hour video recording

AI Human body detection,triggering light alarm when an human is detected,significantly reduce the false alarm rate..

- ◆ **Built-in microphone,support audio and video sync;**
- ◆ **F1.4 advanced aperture,optimize image brightness, with better performance in low-light environments**
- ◆ **Support 3 modes of night vision: Smart dual light/infrared/full-color night vision**
- ◆ **Quick target search for playback**
- ◆ **Aluminum alloy shell, with high heat dissipation**

FICHA TÉCNICA DE PRODUCTO Y MANUAL DE USUARIO EN ESPAÑOL

SEETONG EUROPA S.L.U. CIF B13734926 CALLE JACINTO BENAVENTE 1, PETRER
ALICANTE ESPAÑA CP 03610 TEL +34 667053043 INFO@SMART-DOMOHOUSE.COM

IMPORTADOR PARA MÉXICO: ALEJANDRO ENRIQUE SERRANO GARCIA, RFC
SEGA720208H81, CALLE ANALZINGO 16, COLONIA ANALCO, CUERNAVACA
MORELOS, MÉXICO CP 62166 TEL +52 9986946706 EMAIL
ALEJANDRO.SERRANO@SMART-DOMOHOUSE.COM

Model	3MP	5MP
DSP	HI3516EV200	HI3516EV300
Sensor	3.0 M 1/2.7" SONY IMX307 CMOS sensor	5.0M 1/2.5" SONY IMX335 CMOS sensor
Day/Night	ICR	
Min.Illumination	Low LUX: 0.01LUX @F1.2 (Color) /0.001LUX @F1.2 (B&W)	
Lens	3.6mm fixed lens (6mm Optional) @F1.0	
LED	Φ8*4pcs Warm light	
Noise reduction	Support 2D/3D	
Wide dynamic	Support digital	
Electronic Shutter	1/50(60) s~ 1/10000s	
Audio		
Audio	Built-in microphone	
Alarm IO		
Alarm	Support motion detection	
VIDEO		
Compression	H.265+/H.265X /H.264	
Image output	Main stream:2048*1440@20fps; 1920*1080@25fps	Main stream: 2592*1944@15fps,2560*1440@20fps,1920*1080@25fps
	Sub-stream: 704*576@25fps;	
Frame Rate	1--25FPS (Adjustable)	
Bit Rate	100Kpbs~8Mpbs(Adjustable)	100Kpbs~12Mpbs(Adjustable)
NETWORK		
Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc.	
ONVIF	Support	
Other function	Support WEB,OSD,live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center .reminder and image linkage, support JPEG capture; united remote client monitoring software, Seetong,perfect SDK;	
PC Client & Browser	Uc2, IE	
Mobile Phone	iPhone,iPad,Android Mobile('seetong' app)	
INTERFACE		
Video Output	RJ45	
LAN	1 RJ45 10/100 Ethernet port	
GENERAL		
Working Temperature	-30 C ~ + 50 C	
Working Humidity	0% ~ 90%	
Power Supply	DC12V/POE48V (optional) , 1.0A	
Dimension	190*64*60 mm	
Weight	0.45Kg	